

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



17 DEC 2004

(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/000514 A1


- (51) International Patent Classification?: B27B 33/20, B27G 13/00, B27L 11/00
- (21) International Application Number: PCT/SE2003/000959
- (22) International Filing Date: 11 June 2003 (11.06.2003)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data: 0201865-3 19 June 2002 (19.06.2002) SE
- (71) Applicant (for all designated States except US): JIGGE-SUND TOOLS AB [SE/SE]; Box 6, S-825 21 Iggesund (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BILLER, Sven-Olov [SE/SE]; Slättvägen 8, S-824 40 Hudiksvall (SE).
- (74) Agent: AWAPATENT AB; Box 53, S-826 22 Söderhamn (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PI, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CHIPPER KNIFE



WO 2004/000514 A1

of the cutting edge. The cutting edge (6) of the chipper knife is formed between a timber-guiding surface and a chip-guiding surface, the timber-guiding surface having a varying angle along its length in relation to a plane of rotation in such a way that the angle is greater at the end of the cutting edge located closest to the axis of rotation decreases in the outward direction. The chip-guiding surface of the chipper knife also has a varying angle along its length in relation to a plane of rotation in such a way that the angle is smaller at the end of the cutting edge located closest to the axis of rotation and increases in the outward direction in order to obtain a cutting edge angle between the timber-guiding surface and the chip-guiding surface (13) that is essentially constant along the whole length of the cutting edge.

(57) Abstract: The invention relates to a chipper knife with at least one cutting edge (6) along at least one of its side edges. The chipper knife is adapted to be mounted in chippers of the kind which are used to cut chips of a desired size and shape from pieces of wood or timber (7) and which comprise a tool, in the form of a plane or conical disc, which is arranged for rotation about an axis of rotation and on which a plurality of such chipper knives (2) are mountable in such manner that one end of the cutting edge of the chipper knife is located closer to the axis of rotation of the tool than the opposite end